



CONSTRUCTION MATERIALS

TECHNOLOGIES

LABORATORY TEST REPORT

Report for: Curacreto, SA de CV
 Av. 1 de Mayo #8A
 Mexico City, Mexico 11870

Attention: Jorge A. Robles Ramos

Product Name:	Technoply SBS BFG 300 S	Manufacturer:	Curacreto, SA de CV
Date Received:	Aug. 23, 2017	Sampling:	Curacreto, SA de CV, Mexico City, Mexico
PRI-CMT Project No.:	CURA-001-02-03	Test Dates:	Aug. 25 – Dec. 13, 2017

Purpose: Evaluate the named product for compliance with **ASTM D 6163-00^{ε1}: Standard Specification for Styrene Butadiene Styrene (SBS) Modified Bituminous Sheet Material Using Glass Fiber Reinforcements** and **Florida Building Code Test Protocols for High-Velocity Hurricane Zones, Test Application Standard (TAS) No. 110-2000 Testing Requirements for Physical Properties of Roof Membranes, Insulation, Coatings, and Other Roofing Components.**

Test Methods: Testing was completed in compliance with ASTM D 6163-00^{ε1}: *Standard Specification for Styrene Butadiene Styrene (SBS) Modified Bituminous Sheet Material Using Glass Fiber Reinforcements.* Test methods assigned or referenced include ASTM D 146: *Standard test Methods for Sampling and testing Bitumen-Saturated Felts and Woven Fabrics for Roofing and Waterproofing*; ASTM D 1204: *Standard Test Method for Linear Dimensional Changes of Nonrigid Thermoplastic Sheeting or Film at Elevated Temperature*; ASTM D 4073: *Standard Test Method for Tensile-Tear Strength of Bituminous Roofing Membranes*; ASTM D 4977: *Standard Test Method for Granule Adhesion to Mineral Surfaced Roofing by Abrasion*; ASTM D 5147: *Standard Test Methods for Sampling and Testing Modified Bituminous Sheet Materials*; ASTM D 5636: *Standard Test Method for Low Temperature Unrolling of Felt or Sheet Roofing and Waterproofing Materials*; and ASTM D 5869: *Standard Practice for Dark Oven Heat Exposure of Roofing and Waterproofing Materials.*

Sampling: Product samples were provided by Curacreto, SA de CV from Mexico City, Mexico.

CURA-001-02-03 PRI-CMT Accreditations: AAMA; IAS; Miami-Dade; Florida; Los Angeles; CRRC; UL
 The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Results:

Property	Test Method	Results							Requirement	
									Type I, Grade S	
Physical Properties – Before Heat Conditioning										
Peak Load, (lbf/in-width) 1" x 6" specimens; Cond. 2h @ -0.4±3.6°F; Test @ -0.4±3.6°F; Rate = 0.08in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	134	157	169	191	180	166	22	≥ 70	
	CMD	70	70	74	70	75	72	3	≥ 70	
Elongation, (%) 1" x 6" specimens; Cond. 2h @ -0.4±3.6°F; Test @ -0.4±3.6°F; Rate = 0.08in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	5	5	5	6	5	5	0	≥ 1	
	CMD	5	4	5	4	5	5	0	≥ 1	
Peak Load, (lbf/in-width) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	90	76	107	84	85	88	11	≥ 30	
	CMD	32	29	27	31	34	31	3	≥ 30	
Elongation, (%) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	16	5	12	8	9	10	4	≥ 2	
	CMD	4	4	4	4	5	4	0	≥ 2	
<i>Continued on next page</i>										

CURA-001-02-03

PRI-CMT Accreditations: AAMA; IAS; Miami-Dade; Florida; Los Angeles; CRRC; UL

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Property	Test Method	Results							Requirement	
		1	2	3	4	5	Avg.	St. Dev.	Type I, Grade S	
Ultimate Elongation, (%) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	39	60	53	54	62	54	9	≥ 3	
	CMD	103	77	133	107	108	106	20	≥ 3	
Tear Strength, (lbf) 3" x 8" specimens with assigned notch; Cond. 4h @ 73.4±3.6°F & 50±5%RH; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	148	218	184	145	185	176	30	≥ 35	
	CMD	81	77	81	94	80	82	7	≥ 35	
Low Temperature Flexibility, (Pass/Fail) 1" x 6" specimens; Cond. 2h @ 0°F; Test weathering side away from mandrel; Test 180±5° over 1" ø in 2±1s @ 0°F; Visual Inspection in "flexed" position	ASTM D 5147	1	2	3	4	5			Pass = "none of the specimens show cracking"	
	MD	Pass	Pass	Pass	Pass	Pass			Pass @ 0°F	
	CMD	Pass	Pass	Pass	Pass	Pass			Pass @ 0°F	
Dimensional Stability, (%) 10" x 10" specimens; Cond. 40h @ 73.4±3.6°F & 50±5%RH; Test 24h±15min @ 176±3.6°F	ASTM D 1204/ ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	0.0	0.0	0.0	0.0	0.0	0.0	0.0	≤ 0.5	
	CMD	0.0	0.0	0.0	0.0	0.0	0.0	0.0	≤ 0.5	
<i>Continued on next page</i>										

CURA-001-02-03

PRI-CMT Accreditations: AAMA; IAS; Miami-Dade; Florida; Los Angeles; CRRC; UL

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Property	Test Method	Results							Requirement
		1	2	3	4	5			Type I, Grade S
Compound Stability, [Pass/Fail] 2.0±0.05" x 3.0±0.05" specimens; Cond. 4h @ 73.4±3.6°F & 50±5%RH; Test 2h,15min±5min @ 215±5°F	ASTM D 5147	1	2	3	4	5			Pass = no failures showing signs of flowing, dripping, or drop formation
	MD	Pass	Pass	Pass	Pass	Pass			Pass
	CMD	Pass	Pass	Pass	Pass	Pass			Pass
Granule Embedment (g) Grade G products only; 2" x 9" specimens; Cond. 30min @ 73.4±3.6°F; Test 50 complete cycles	ASTM D 4977/ ASTM D 5147	1	2	Avg.					
		NA	NA	NA					NA
Physical Properties – After Heat Conditioning									
Heat Conditioning Exposure: 90±0.25d @ 158±5°F	ASTM D 5869/ ASTM D 5147								
Peak Load, (lbf/in-width) 1" x 6" specimens; Cond. 2h @ -0.4±3.6°F; Test @ -0.4±3.6°F; Rate = 0.08in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.	
	MD	206	187	208	200	202	201	8	≥ 70
	CMD	89	71	71	74	70	75	8	≥ 70
Elongation, (%) 1" x 6" specimens; Cond. 2h @ -0.4±3.6°F; Test @ -0.4±3.6°F; Rate = 0.08in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.	
	MD	6	9	7	5	6	6	2	≥ 1
	CMD	5	4	4	5	4	4	0	≥ 1
<i>Continued on next page</i>									

CURA-001-02-03

PRI-CMT Accreditations: AAMA; IAS; Miami-Dade; Florida; Los Angeles; CRRC; UL

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Property	Test Method	Results							Requirement
		1	2	3	4	5	Avg.	St. Dev.	Type I, Grade S
Peak Load, (lbf/in-width) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.	
	MD	147	166	162	160	161	159	7	≥ 30
	CMD	50	48	46	57	56	57	11	≥ 30
Elongation, (%) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.	
	MD	7	8	8	7	8	8	1	≥ 2
	CMD	4	3	5	4	4	4	1	≥ 2
Ultimate Elongation, (%) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.	
	MD	30	31	26	31	20	28	5	≥ 3
	CMD	41	32	31	29	40	35	5	≥ 3
Low Temperature Flexibility, [Pass/Fail] 1" x 6" specimens; Cond. 2h @ 0°F; Test weathering side away from mandrel; Test 180±5° over 1" ø in 2±1s @ 0°F; Visual Inspection in "flexed" position	ASTM D 5147	1	2	3	4	5			Pass = "none of the specimens show cracking"
	MD	Pass	Pass	Pass	Pass	Pass			Pass @ 0°F
	CMD	Pass	Pass	Pass	Pass	Pass			Pass @ 0°F
<i>Continued on next page</i>									

CURA-001-02-03

PRI-CMT Accreditations: AAMA; IAS; Miami-Dade; Florida; Los Angeles; CRRC; UL

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Property	Test Method	Results					Requirement			
							Type I, Grade S			
Physical Properties – Other										
Unrolling, [Pass/Fail] 10±1/8" x 18±1/8" specimens; Cond. 24h @ 73.4±3.6°F & 50±5%RH; Test Cond. 2h @ Temp±1°F; Test unroll in 4-6s; Visual Inspection in "unrolled" position	ASTM D 5636/ ASTM D 5147	1	2	3	4					Pass = "finished product shall not crack nor be so sticky as to cause tearing or other material damage upon being unrolled at any temperature between 40 and 140°F"
		Pass	Pass	Pass	Pass					Pass
Dimensions and Masses										
Thickness, (mils) 27-1/2" x manufacture width; 5 measurement points	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
		122	120	124	119	121	121	2	≥ 80	
Net Mass, (lb/100ft ²) 1 specimen; manufacture roll	ASTM D 228									
		72							≥ 45	
Bottom Coating Thickness, (mils) Heat Welding Application Products; 6" x manufacture width; 5 measurement points	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
		N/A	N/A	N/A	N/A	N/A	N/A	N/A	Not Required	

Notes: 1) N/A indicates Not Applicable; NT indicates Not Tested; As Agreed: as agreed by buyer and seller

CURA-001-02-03

PRI-CMT Accreditations: AAMA; IAS; Miami-Dade; Florida; Los Angeles; CRRC; UL

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Statement of Compliance:

The product tested has demonstrated compliance with the physical property requirements of ASTM D 6163-00^{e1}: *Standard Specification for Styrene Butadiene Styrene (SBS) Modified Bituminous Sheet Material Using Glass Fiber Reinforcements, Type I* and Florida Building Code Test Protocols for High-Velocity Hurricane Zones, Test Application Standard (TAS) No. 110-2000 *Testing Requirements for Physical Properties of Roof Membranes, Insulation, Coatings, and Other Roofing Components*. The laboratory test results presented in this report are representative of the material supplied.

Signed: _____
Date: _____



Zachary R. Priest, P.E.
Florida Registered Professional Engineer
PE No.: 74021

STATE OF FLORIDA
PROFESSIONAL ENGINEER

Report Issue History:

Issue #	Date	Pages	Revision Description (if applicable)
Original	12/27/2017	7	NA

CURA-001-02-03

PRI-CMT Accreditations: AAMA; IAS; Miami-Dade; Florida; Los Angeles; CRRC; UL

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

END OF REPORT

CURA-001-02-03

PRI-CMT Accreditations: AAMA; IAS; Miami-Dade; Florida; Los Angeles; CRRC; UL

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.



CONSTRUCTION MATERIALS

TECHNOLOGIES

LABORATORY TEST REPORT

Report for: Curacreto, SA de CV
Av. 1 de Mayo #8A
Mexico City, Mexico 11870

Attention: Jorge A. Robles Ramos

Product Name: Technoply SBS BP 300 S	Manufacturer: Curacreto, SA de CV
Date Received: Sep. 14, 2017	Sampling: Curacreto, SA de CV, Mexico City, Mexico
PRI-CMT Project No.: CURA-004-02-03	Test Dates: Sep. 21, 2017 – Jan. 4, 2018

Purpose: Evaluate the named products for compliance with **ASTM D 6164: Standard Specification for Styrene Butadiene Styrene (SBS) Modified Bituminous Sheet Material Using Polyester Reinforcements** as required by the **Florida Building Code Test Protocols for High-Velocity Hurricane Zones, Test Application Standard (TAS) No. 110-2000 Testing Requirements for Physical Properties of Roof Membranes, Insulation, Coatings, and Other Roofing Components.**

Test Methods: Testing was completed in compliance with ASTM D 6164-05^{e1} and ASTM D 6164/D 6164M-11: *Standard Specification for Styrene Butadiene Styrene (SBS) Modified Bituminous Sheet Material Using Polyester Reinforcements.* Test methods assigned or referenced include ASTM D 146: *Standard test Methods for Sampling and testing Bitumen-Saturated Felts and Woven Fabrics for Roofing and Waterproofing;* ASTM D 1204: *Standard Test Method for Linear Dimensional Changes of Nonrigid Thermoplastic Sheet or Film at Elevated Temperature;* ASTM D 4073: *Standard Test Method for Tensile-Tear Strength of Bituminous Roofing Membranes;* ASTM D 4977: *Standard Test Method for Granule Adhesion to Mineral Surfaced Roofing by Abrasion;* ASTM D 5147: *Standard Test Methods for Sampling and Testing Modified Bituminous Sheet Materials;* ASTM D 5636: *Standard Test Method for Low Temperature Unrolling of Felt or Sheet Roofing and Waterproofing Materials;* and ASTM D 5869: *Standard Practice for Dark Oven Heat Exposure of Roofing and Waterproofing Materials.*

Sampling: Product samples were provided by Curacreto, SA de CV from Mexico City, Mexico

CURA-004-02-03 PRI-CMT Accreditations: AAMA; IAS; Miami-Dade; Florida; Los Angeles; CRRC; UL
The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Results:

Property	Test Method	Results							Requirement	
									Type I, Grade S	
Physical Properties – Before Heat Conditioning										
Peak Load, (lbf/in-width) 1" x 6" specimens; Cond. 2h @ -0.4±3.6°F; Test @ -0.4±3.6°F; Rate = 0.08in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	106	98	106	114	104	106	6	≥ 70	
	CMD	104	86	94	106	101	98	8	≥ 70	
Elongation, (%) 1" x 6" specimens; Cond. 2h @ -0.4±3.6°F; Test @ -0.4±3.6°F; Rate = 0.08in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	48	36	42	47	42	43	5	≥ 20	
	CMD	46	35	37	41	43	41	5	≥ 20	
Peak Load, (lbf/in-width) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	88	79	86	90	86	86	4	≥ 50	
	CMD	65	69	63	65	73	67	4	≥ 50	
Elongation, (%) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	59	51	54	55	47	53	5	≥ 35	
	CMD	54	60	57	66	63	60	5	≥ 35	
<i>Continued on next page</i>										

CURA-004-02-03

PRI-CMT Accreditations: AAMA; IAS; Miami-Dade; Florida; Los Angeles; CRRC; UL

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Property	Test Method	Results							Requirement	
		1	2	3	4	5	Avg.	St. Dev.	Type I, Grade S	
Ultimate Elongation, (%) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	98	76	71	77	73	79	11	≥ 38	
	CMD	78	96	95	89	82	88	8	≥ 38	
Tear Strength, (lbf) 3" x 8" specimens with assigned notch; Cond. 4h @ 73.4±3.6°F & 50±5%RH; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	112	97	105	99	98	102	6	≥ 55	
	CMD	139	141	134	136	131	136	4	≥ 55	
Low Temperature Flexibility, (Pass/Fail) 1" x 6" specimens; Cond. 2h @ 0°F; Test weathering side away from mandrel; Test 180±5° over 1" ø in 2±1s @ 0°F; Visual Inspection in "flexed" position	ASTM D 5147	1	2	3	4	5			Pass = "none of the specimens show cracking"	
	MD	Pass	Pass	Pass	Pass	Pass			Pass @ 0°F	
	CMD	Pass	Pass	Pass	Pass	Pass			Pass @ 0°F	
Dimensional Stability, (%) 10" x 10" specimens; Cond. 40h @ 73.4±3.6°F & 50±5%RH; Test 24h±15min @ 176±3.6°F	ASTM D 1204/ ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	0.2	0.0	0.1	0.1	0.1	0.1	0.1	≤ 1	
	CMD	0.2	0.1	0.2	0.2	0.1	0.1	0.1	≤ 1	

Continued on next page

CURA-004-02-03

PRI-CMT Accreditations: AAMA; IAS; Miami-Dade; Florida; Los Angeles; CRRC; UL

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Property	Test Method	Results							Requirement
		1	2	3	4	5		Type I, Grade S	
Compound Stability, [Pass/Fail] 2.0±0.05" x 3.0±0.05" specimens; Cond. 4h @ 73.4±3.6°F & 50±5%RH; Test 2h,15min±5min @ 215±5°F	ASTM D 5147	1	2	3	4	5			Pass = no failures showing signs of flowing, dripping, or drop formation
	MD	Pass	Pass	Pass	Pass	Pass			Pass
	CMD	Pass	Pass	Pass	Pass	Pass			Pass
Granule Embedment (g) Grade G products only; 2" x 9" specimens; Cond. 30min @ 73.4±3.6°F; Test 50 complete cycles	ASTM D 4977/ ASTM D 5147	1	2	Avg.					
		N/A	N/A	N/A					≤ 2
Physical Properties – After Heat Conditioning									
Heat Conditioning Exposure: 90±0.25d @ 158±5°F	ASTM D 5869/ ASTM D 5147								
Peak Load, (lbf/in-width) 1" x 6" specimens; Cond. 2h @ -0.4±3.6°F; Test @ -0.4±3.6°F; Rate = 0.08in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.	
	MD	107	96	100	100	101	101	4	≥ 70
	CMD	63	76	84	76	75	75	8	≥ 70
Elongation, (%) 1" x 6" specimens; Cond. 2h @ -0.4±3.6°F; Test @ -0.4±3.6°F; Rate = 0.08in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.	
	MD	36	33	36	32	36	35	2	≥ 20
	CMD	24	33	35	27	37	31	6	≥ 20
<i>Continued on next page</i>									

CURA-004-02-03

PRI-CMT Accreditations: AAMA; IAS; Miami-Dade; Florida; Los Angeles; CRRC; UL

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Property	Test Method	Results							Requirement
		1	2	3	4	5	Avg.	St. Dev.	Type I, Grade S
Peak Load, (lbf/in-width) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.	
	MD	87	88	89	89	94	89	3	≥ 50
	CMD	61	62	60	59	66	62	3	≥ 50
Elongation, (%) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.	
	MD	49	48	48	50	58	51	4	≥ 35
	CMD	55	48	52	42	65	52	8	≥ 35
Ultimate Elongation, (%) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.	
	MD	54	51	51	53	60	54	3	≥ 38
	CMD	59	51	56	48	74	58	10	≥ 38
Low Temperature Flexibility, [Pass/Fail] 1" x 6" specimens; Cond. 2h @ 0°F; Test weathering side away from mandrel; Test 180±5° over 1" ø in 2±1s @ 0°F; Visual Inspection in "flexed" position	ASTM D 5147	1	2	3	4	5			Pass = "none of the specimens show cracking"
	MD	Pass	Pass	Pass	Pass	Pass			Pass @ 0°F
	CMD	Pass	Pass	Pass	Pass	Pass			Pass @ 0°F
<i>Continued on next page</i>									

CURA-004-02-03

PRI-CMT Accreditations: AAMA; IAS; Miami-Dade; Florida; Los Angeles; CRRC; UL

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Property	Test Method	Results					Requirement			
							Type I, Grade S			
Physical Properties – Other										
Unrolling, [Pass/Fail] 10±1/8" x 18±1/8" specimens; Cond. 24h @ 73.4±3.6°F & 50±5%RH; Test Cond. 2h @ Temp±1°F; Test unroll in 4-6s; Visual Inspection in "unrolled" position	ASTM D 5636/ ASTM D 5147	1	2	3	4					Pass = "finished product shall not crack nor be so sticky as to cause tearing or other material damage upon being unrolled at any temperature between 40 and 140°F"
		Pass	Pass	Pass	Pass					
Dimensions and Masses										
Thickness, (mils) 27-1/2" x manufacture width; 5 measurement points	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
		136	129	133	137	136	134	4	≥ 85	
Net Mass, (lb/100ft ²) 1 specimen; manufacture roll	ASTM D 228									
		69							≥ 54	
Bottom Coating Thickness, (mils) Heat Welding Application Products; 6" x manufacture width; 5 measurement points	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
		69	63	60	69	65	65	4	≥ 40	

Notes: 1) N/A indicates Not Applicable; NT indicates Not Tested; As Agreed: as agreed by buyer and seller

CURA-004-02-03

PRI-CMT Accreditations: AAMA; IAS; Miami-Dade; Florida; Los Angeles; CRRC; UL

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Statement of Compliance:

The products tested have demonstrated compliance with the physical property requirements of ASTM D 6164-05^{e1} and ASTM D 6164/D 6164M-11: *Standard Specification for Styrene Butadiene Styrene (SBS) Modified Bituminous Sheet Material Using Polyester Reinforcements, Type I* and Florida Building Code Test Protocols for High-Velocity Hurricane Zones, Test Application Standard (TAS) No. 110-2000 *Testing Requirements for Physical Properties of Roof Membranes, Insulation, Coatings, and Other Roofing Components*. The laboratory test results presented in this report are representative of the material supplied.

Signed: 
Zachary R. Priest, P.E.
Florida Registered Professional Engineer
PE No. 74021

Date: 



Report Issue History:

Issue #	Date	Pages	Revision Description (if applicable)
Original	01/09/2018	7	N/A

END OF REPORT

CURA-004-02-03

PRI-CMT Accreditations: AAMA; IAS; Miami-Dade; Florida; Los Angeles; CRRC; UL

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

CURA-004-02-03

PRI-CMT Accreditations: AAMA; IAS; Miami-Dade; Florida; Los Angeles; CRRC; UL

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.



CONSTRUCTION MATERIALS

TECHNOLOGIES

LABORATORY TEST REPORT

Report for: Curacreto, SA de CV
Av. 1 de Mayo #8A
Mexico City, Mexico 11870

Attention: Jorge A. Robles Ramos

Product Name: Technoply SBS FR SP 400 G	Manufacturer: Curacreto, SA de CV
Date Received: Sep. 14, 2017	Sampling: Curacreto, SA de CV, Mexico City, Mexico
PRI-CMT Project No.: CURA-004-02-06	Test Dates: Oct. 11, 2017 – Feb. 1, 2018

Purpose: Evaluate the named products for compliance with **ASTM D 6164: Standard Specification for Styrene Butadiene Styrene (SBS) Modified Bituminous Sheet Material Using Polyester Reinforcements** and **ASTM D 5147 Section 13: Accelerated Weathering** as required by the **Florida Building Code Test Protocols for High-Velocity Hurricane Zones, Test Application Standard (TAS) No. 110-2000 Testing Requirements for Physical Properties of Roof Membranes, Insulation, Coatings, and Other Roofing Components.**

Test Methods: Testing was completed in compliance with ASTM D 6164-05^{e1} and ASTM D 6164/D 6164M-11: *Standard Specification for Styrene Butadiene Styrene (SBS) Modified Bituminous Sheet Material Using Polyester Reinforcements.* Test methods assigned or referenced include ASTM D 146: *Standard test Methods for Sampling and testing Bitumen-Saturated Felts and Woven Fabrics for Roofing and Waterproofing;* ASTM D 1204: *Standard Test Method for Linear Dimensional Changes of Nonrigid Thermoplastic Sheet or Film at Elevated Temperature;* ASTM D 4073: *Standard Test Method for Tensile-Tear Strength of Bituminous Roofing Membranes;* ASTM D 4977: *Standard Test Method for Granule Adhesion to Mineral Surfaced Roofing by Abrasion;* ASTM D 5147: *Standard Test Methods for Sampling and Testing Modified Bituminous Sheet Materials;* ASTM D 5636: *Standard Test Method for Low Temperature Unrolling of Felt or Sheet Roofing and Waterproofing Materials;* and ASTM D 5869: *Standard Practice for Dark Oven Heat Exposure of Roofing and Waterproofing Materials.*

Sampling: Product samples were provided by Curacreto, SA de CV from Mexico City, Mexico.

CURA-004-02-06 PRI-CMT Accreditations: AAMA; IAS; Miami-Dade; Florida; Los Angeles; CRRC; UL
The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Results:

Property	Test Method	Results							Requirement
									Type I, Grade G
Physical Properties – Before Heat Conditioning									
Peak Load, (lbf/in-width) 1" x 6" specimens; Cond. 2h @ -0.4±3.6°F; Test @ -0.4±3.6°F; Rate = 0.08in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.	
	MD	114	102	101	113	113	109	7	≥ 70
	CMD	77	75	79	92	84	81	7	≥ 70
Elongation, (%) 1" x 6" specimens; Cond. 2h @ -0.4±3.6°F; Test @ -0.4±3.6°F; Rate = 0.08in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.	
	MD	40	35	39	46	43	41	4	≥ 20
	CMD	21	26	26	38	32	29	7	≥ 20
Peak Load, (lbf/in-width) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.	
	MD	85	92	92	79	81	86	6	≥ 50
	CMD	60	61	56	56	62	59	3	≥ 50
Elongation, (%) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.	
	MD	53	50	63	56	47	54	6	≥ 35
	CMD	54	58	51	58	57	56	3	≥ 35
<i>Continued on next page</i>									

CURA-004-02-06

PRI-CMT Accreditations: AAMA; IAS; Miami-Dade; Florida; Los Angeles; CRRC; UL

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Property	Test Method	Results							Requirement	
		1	2	3	4	5	Avg.	St. Dev.	Type I, Grade G	
Ultimate Elongation, (%) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	81	85	95	83	75	84	7	≥ 38	
	CMD	78	82	71	77	83	78	5	≥ 38	
Tear Strength, (lbf) 3" x 8" specimens with assigned notch; Cond. 4h @ 73.4±3.6°F & 50±5%RH; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	111	118	108	98	95	106	10	≥ 55	
	CMD	121	144	125	145	130	133	11	≥ 55	
Low Temperature Flexibility, (Pass/Fail) 1" x 6" specimens; Cond. 2h @ 0°F; Test weathering side away from mandrel; Test 180±5° over 1" ø in 2±1s @ 0°F; Visual Inspection in "flexed" position	ASTM D 5147	1	2	3	4	5			Pass = "none of the specimens show cracking"	
	MD	Pass	Pass	Pass	Pass	Pass			Pass @ 0°F	
	CMD	Pass	Pass	Pass	Pass	Pass			Pass @ 0°F	
Dimensional Stability, (%) 10" x 10" specimens; Cond. 40h @ 73.4±3.6°F & 50±5%RH; Test 24h±15min @ 176±3.6°F	ASTM D 1204/ ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	0.1	0.1	0.0	0.0	0.1	0.1	0.1	≤ 1	
	CMD	0.1	0.1	0.0	0.0	0.0	0.0	0.0	≤ 1	
<i>Continued on next page</i>										

CURA-004-02-06

PRI-CMT Accreditations: AAMA; IAS; Miami-Dade; Florida; Los Angeles; CRRC; UL

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Property	Test Method	Results							Requirement
									Type I, Grade G
Compound Stability, [Pass/Fail] 2.0±0.05" x 3.0±0.05" specimens; Cond. 4h @ 73.4±3.6°F & 50±5%RH; Test 2h,15min±5min @ 215±5°F	ASTM D 5147	1	2	3	4	5			Pass = no failures showing signs of flowing, dripping, or drop formation
	MD	Pass	Pass	Pass	Pass	Pass			Pass
	CMD	Pass	Pass	Pass	Pass	Pass			Pass
Granule Embedment (g) Grade G products only; 2" x 9" specimens; Cond. 30min @ 73.4±3.6°F; Test 50 complete cycles	ASTM D 4977/ ASTM D 5147	1	2	Avg.					
		1	1	1					≤ 2
Physical Properties – After Heat Conditioning									
Heat Conditioning Exposure: 90±0.25d @ 158±5°F	ASTM D 5869/ ASTM D 5147								
Peak Load, (lbf/in-width) 1" x 6" specimens; Cond. 2h @ -0.4±3.6°F; Test @ -0.4±3.6°F; Rate = 0.08in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.	
	MD	91	102	94	96	107	98	6	≥ 70
	CMD	67	69	67	73	74	70	4	≥ 70
Elongation, (%) 1" x 6" specimens; Cond. 2h @ -0.4±3.6°F; Test @ -0.4±3.6°F; Rate = 0.08in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.	
	MD	29	31	31	21	34	29	5	≥ 20
	CMD	22	24	30	28	21	25	4	≥ 20
<i>Continued on next page</i>									

CURA-004-02-06

PRI-CMT Accreditations: AAMA; IAS; Miami-Dade; Florida; Los Angeles; CRRC; UL

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Property	Test Method	Results							Requirement
		1	2	3	4	5	Avg.	St. Dev.	Type I, Grade G
Peak Load, (lbf/in-width) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.	
	MD	90	92	96	90	97	93	3	≥ 50
	CMD	68	63	62	60	60	63	3	≥ 50
Elongation, (%) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.	
	MD	40	40	54	47	50	46	6	≥ 35
	CMD	53	42	51	49	33	46	8	≥ 35
Ultimate Elongation, (%) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.	
	MD	48	46	59	55	53	52	5	≥ 38
	CMD	56	47	56	55	41	51	7	≥ 38
Low Temperature Flexibility, [Pass/Fail] 1" x 6" specimens; Cond. 2h @ 0°F; Test weathering side away from mandrel; Test 180±5° over 1" ø in 2±1s @ 0°F; Visual Inspection in "flexed" position	ASTM D 5147	1	2	3	4	5			Pass = "none of the specimens show cracking"
	MD	Pass	Pass	Pass	Pass	Pass			Pass @ 0°F
	CMD	Pass	Pass	Pass	Pass	Pass			Pass @ 0°F
<i>Continued on next page</i>									

CURA-004-02-06

PRI-CMT Accreditations: AAMA; IAS; Miami-Dade; Florida; Los Angeles; CRRC; UL

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Property	Test Method	Results					Requirement			
		1	2	3	4		Type I, Grade G			
Physical Properties – Other										
Unrolling, [Pass/Fail] 10±1/8" x 18±1/8" specimens; Cond. 24h @ 73.4±3.6°F & 50±5%RH; Test Cond. 2h @ Temp±1°F; Test unroll in 4-6s; Visual Inspection in "unrolled" position	ASTM D 5636/ ASTM D 5147	1	2	3	4					Pass = "finished product shall not crack nor be so sticky as to cause tearing or other material damage upon being unrolled at any temperature between 40 and 140°F"
	Temp=40°F	Pass	Pass	Pass	Pass					Pass
	Temp=140°F	Pass	Pass	Pass	Pass					Pass
Dimensions and Masses										
Thickness, (mils) 27-1/2" x manufacture width; 5 measurement points	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
		179	181	180	172	170	176	5	≥ 130	
Net Mass, (lb/100ft ²) 1 specimen; manufacture roll	ASTM D 228	90							≥ 75	
Bottom Coating Thickness, (mils) Heat Welding Application Products; 6" x manufacture width; 5 measurement points	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
		85	75	89	71	75	79	8	≥ 40	
<i>Continued on next page</i>										

CURA-004-02-06

PRI-CMT Accreditations: AAMA; IAS; Miami-Dade; Florida; Los Angeles; CRRC; UL

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Property	Test Method	Results							Requirement	
									Type I, Grade G	
Physical Properties – After Accelerated Weathering										
Xenon Arc Weathering Exposure: 83±0.35d @ Cycle A	ASTM D 4798/ ASTM D 5147									
Peak Load, (lbf/in-width) 1" x 6" specimens; Cond. 2h @ -0.4±3.6°F; Test @ -0.4±3.6°F; Rate = 0.08in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	105	91	87	102	86	94	9	≥ 70	
	CMD	81	71	61	73	91	75	11	≥ 70	
Elongation, (%) 1" x 6" specimens; Cond. 2h @ -0.4±3.6°F; Test @ -0.4±3.6°F; Rate = 0.08in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	35	29	24	33	22	29	6	≥ 20	
	CMD	40	31	22	33	42	34	8	≥ 20	
Peak Load, (lbf/in-width) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	102	94	93	95	94	96	4	≥ 50	
	CMD	66	72	67	55	65	65	6	≥ 50	
Elongation, (%) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	54	57	51	51	67	56	7	≥ 35	
	CMD	59	63	56	37	52	53	10	≥ 35	
<i>Continued on next page</i>										

CURA-004-02-06

PRI-CMT Accreditations: AAMA; IAS; Miami-Dade; Florida; Los Angeles; CRRC; UL

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Property	Test Method	Results							Requirement
		1	2	3	4	5	Avg.	St. Dev.	Type I, Grade G
Ultimate Elongation, (%) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.	
	MD	58	59	53	54	74	60	9	≥ 38
	CMD	63	66	61	46	57	58	8	≥ 38
Low Temperature Flexibility, [Pass/Fail] 1" x 6" specimens; Cond. 2h @ 0°F; Test weathering side away from mandrel; Test 180±5° over 1" ø in 2±1s @ 0°F; Visual Inspection in "flexed" position	ASTM D 5147	1	2	3	4	5			Pass = "none of the specimens show cracking"
	MD	Pass	Pass	Pass	Pass	Pass			Pass @ 0°F
	CMD	Pass	Pass	Pass	Pass	Pass			Pass @ 0°F

Notes: 1) N/A indicates Not Applicable; NT indicates Not Tested; As Agreed: as agreed by buyer and seller

CURA-004-02-06

PRI-CMT Accreditations: AAMA; IAS; Miami-Dade; Florida; Los Angeles; CRRC; UL

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Statement of Compliance:

The products tested have demonstrated compliance with the physical property requirements of ASTM D 6164-05^{e1} and ASTM D 6164/D 6164M-11: *Standard Specification for Styrene Butadiene Styrene (SBS) Modified Bituminous Sheet Material Using Polyester Reinforcements, Type I* and Florida Building Code Test Protocols for High-Velocity Hurricane Zones, Test Application Standard (TAS) No. 110-2000 *Testing Requirements for Physical Properties of Roof Membranes, Insulation, Coatings, and Other Roofing Components*. The laboratory test results presented in this report are representative of the material supplied.

Signed: 
Zachary R. Priest, P.E.
Florida Registered Professional Engineer
PE No.: 74021

Date: 



Report Issue History:

Issue #	Date	Pages	Revision Description (if applicable)
Original	02/05/2018	9	N/A

END OF REPORT

CURA-004-02-06

PRI-CMT Accreditations: AAMA; IAS; Miami-Dade; Florida; Los Angeles; CRRC; UL

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.



CONSTRUCTION MATERIALS

TECHNOLOGIES

LABORATORY TEST REPORT

Report for: Curacreto, SA de CV
Av. 1 de Mayo #8A
Mexico City, Mexico 11870

Attention: Jorge A. Robles Ramos

Product Name:	Technoply SBS SP 400 G	Manufacturer:	Curacreto, SA de CV
Date Received:	Nov. 8, 2017	Sampling:	Curacreto, SA de CV, Mexico City, Mexico
PRI-CMT Project No.:	CURA-004-02-08	Test Dates:	Dec. 21, 2017 – Apr. 20, 2018

Purpose: Evaluate the named products for compliance with **ASTM D 6164: Standard Specification for Styrene Butadiene Styrene (SBS) Modified Bituminous Sheet Material Using Polyester Reinforcements** and **ASTM D 5147 Section 13: Accelerated Weathering** as required by the **Florida Building Code Test Protocols for High-Velocity Hurricane Zones, Test Application Standard (TAS) No. 110-2000 Testing Requirements for Physical Properties of Roof Membranes, Insulation, Coatings, and Other Roofing Components.**

Test Methods: Testing was completed in compliance with ASTM D 6164-05^{e1} and ASTM D 6164/D 6164M-11: *Standard Specification for Styrene Butadiene Styrene (SBS) Modified Bituminous Sheet Material Using Polyester Reinforcements.* Test methods assigned or referenced include ASTM D 146: *Standard test Methods for Sampling and testing Bitumen-Saturated Felts and Woven Fabrics for Roofing and Waterproofing;* ASTM D 1204: *Standard Test Method for Linear Dimensional Changes of Nonrigid Thermoplastic Sheet or Film at Elevated Temperature;* ASTM D 4073: *Standard Test Method for Tensile-Tear Strength of Bituminous Roofing Membranes;* ASTM D 4977: *Standard Test Method for Granule Adhesion to Mineral Surfaced Roofing by Abrasion;* ASTM D 5147: *Standard Test Methods for Sampling and Testing Modified Bituminous Sheet Materials;* ASTM D 5636: *Standard Test Method for Low Temperature Unrolling of Felt or Sheet Roofing and Waterproofing Materials;* and ASTM D 5869: *Standard Practice for Dark Oven Heat Exposure of Roofing and Waterproofing Materials.*

Sampling: Product samples were provided by Curacreto, SA de CV from Mexico City, Mexico.

CURA-004-02-08

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Results:

Property	Test Method	Results							Requirement	
									Type I, Grade G	
Physical Properties – Before Heat Conditioning										
Peak Load, (lbf/in-width) 1" x 6" specimens; Cond. 2h @ -0.4±3.6°F; Test @ -0.4±3.6°F; Rate = 0.08in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	97	104	120	132	117	114	14	≥ 70	
	CMD	79	73	77	85	69	77	6	≥ 70	
Elongation, (%) 1" x 6" specimens; Cond. 2h @ -0.4±3.6°F; Test @ -0.4±3.6°F; Rate = 0.08in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	37	41	46	52	42	44	6	≥ 20	
	CMD	34	25	22	35	13	26	9	≥ 20	
Peak Load, (lbf/in-width) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	91	87	89	86	83	89	3	≥ 50	
	CMD	66	64	75	63	62	66	5	≥ 50	
Elongation, (%) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	48	54	58	51	58	54	4	≥ 35	
	CMD	58	54	62	57	61	58	3	≥ 35	
<i>Continued on next page</i>										

CURA-004-02-08

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Property	Test Method	Results							Requirement	
		1	2	3	4	5	Avg.	St. Dev.	Type I, Grade G	
Ultimate Elongation, (%) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	141	89	311	339	90	194	122	≥ 38	
	CMD	81	78	85	79	83	81	3	≥ 38	
Tear Strength, (lbf) 3" x 8" specimens with assigned notch; Cond. 4h @ 73.4±3.6°F & 50±5%RH; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	90	109	98	94	101	98	7	≥ 55	
	CMD	120	128	133	115	122	124	7	≥ 55	
Low Temperature Flexibility, (Pass/Fail) 1" x 6" specimens; Cond. 2h @ 0°F; Test weathering side away from mandrel; Test 180±5° over 1" ø in 2±1s @ 0°F; Visual Inspection in "flexed" position	ASTM D 5147	1	2	3	4	5			Pass = "none of the specimens show cracking"	
	MD	Pass	Pass	Pass	Pass	Pass			Pass @ 0°F	
	CMD	Pass	Pass	Pass	Pass	Pass			Pass @ 0°F	
Dimensional Stability, (%) 10" x 10" specimens; Cond. 40h @ 73.4±3.6°F & 50±5%RH; Test 24h±15min @ 176±3.6°F	ASTM D 1204/ ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	0.1	0.0	0.0	0.1	0.0	0.0	0.0	≤ 1	
	CMD	0.0	0.0	0.0	0.0	0.0	0.0	0.0	≤ 1	
<i>Continued on next page</i>										

CURA-004-02-08

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Property	Test Method	Results							Requirement	
		1	2	3	4	5			Type I, Grade G	
Compound Stability, [Pass/Fail] 2.0±0.05" x 3.0±0.05" specimens; Cond. 4h @ 73.4±3.6°F & 50±5%RH; Test 2h,15min±5min @ 215±5°F	ASTM D 5147	1	2	3	4	5				Pass = no failures showing signs of flowing, dripping, or drop formation
	MD	Pass	Pass	Pass	Pass	Pass				Pass
	CMD	Pass	Pass	Pass	Pass	Pass				Pass
Granule Embedment (g) Grade G products only; 2" x 9" specimens; Cond. 30min @ 73.4±3.6°F; Test 50 complete cycles	ASTM D 4977/ ASTM D 5147	1	2	AVG.						
		2.6	1.2	1.9						≤ 2
Physical Properties – After Heat Conditioning										
Heat Conditioning Exposure: 90±0.25d @ 158±5°F	ASTM D 5869/ ASTM D 5147									
Peak Load, (lbf/in-width) 1" x 6" specimens; Cond. 2h @ -0.4±3.6°F; Test @ -0.4±3.6°F; Rate = 0.08in/min ±3%	ASTM D 5147	1	2	3	4	5	AVG.	St. Dev.		
	MD	95	110	96	110	118	106	10		≥ 70
	CMD	75	79	74	86	75	78	5		≥ 70
Elongation, (%) 1" x 6" specimens; Cond. 2h @ -0.4±3.6°F; Test @ -0.4±3.6°F; Rate = 0.08in/min ±3%	ASTM D 5147	1	2	3	4	5	AVG.	St. Dev.		
	MD	23	36	15	26	35	27	9		≥ 20
	CMD	24	29	38	39	36	33	7		≥ 20
<i>Continued on next page</i>										

CURA-004-02-08

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Property	Test Method	Results							Requirement	
		1	2	3	4	5	Avg.	St. Dev.	Type I, Grade G	
Peak Load, (lbf/in-width) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	102	85	95	92	97	94	7	≥ 50	
	CMD	80	70	72	65	68	71	6	≥ 50	
Elongation, (%) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	59	44	52	49	54	51	6	≥ 35	
	CMD	60	45	56	51	50	52	6	≥ 35	
Ultimate Elongation, (%) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	62	49	53	51	56	54	5	≥ 38	
	CMD	64	50	66	54	53	57	7	≥ 38	
Low Temperature Flexibility, [Pass/Fail] 1" x 6" specimens; Cond. 2h @ 0°F; Test weathering side away from mandrel; Test 180±5° over 1" ø in 2±1s @ 0°F; Visual Inspection in "flexed" position	ASTM D 5147	1	2	3	4	5			Pass = "none of the specimens show cracking"	
	MD	Pass	Pass	Pass	Pass	Pass			Pass @ 0°F	
	CMD	Pass	Pass	Pass	Pass	Pass			Pass @ 0°F	
<i>Continued on next page</i>										

CURA-004-02-08

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Property	Test Method	Results					Requirement			
							Type I, Grade G			
Physical Properties – Other										
Unrolling, [Pass/Fail] 10±1/8" x 18±1/8" specimens; Cond. 24h @ 73.4±3.6°F & 50±5%RH; Test Cond. 2h @ Temp±1°F; Test unroll in 4-6s; Visual Inspection in "unrolled" position	ASTM D 5636/ ASTM D 5147	1	2	3	4			Pass = "finished product shall not crack nor be so sticky as to cause tearing or other material damage upon being unrolled at any temperature between 40 and 140°F"		
	Temp=40°F	Pass	Pass	Pass	Pass			Pass		
	Temp=140°F	Pass	Pass	Pass	Pass			Pass		
Dimensions and Masses										
Thickness, (mils) 27-1/2" x manufacture width; 5 measurement points	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
		174	172	171	171	171	172	2	≥ 130	
Net Mass, (lb/100ft ²) 1 specimen; manufacture roll	ASTM D 228									
		89								≥ 75
Bottom Coating Thickness, (mils) Heat Welding Application Products; 6" x manufacture width; 5 measurement points	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
		89	78	87	82	78	83	5	≥ 40	
<i>Continued on next page</i>										

CURA-004-02-08

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Property	Test Method	Results							Requirement	
									Type I, Grade G	
Physical Properties – After Accelerated Weathering										
Xenon Arc Weathering Exposure: 83±0.35d @ Cycle A	ASTM D 4798/ ASTM D 5147									
Peak Load, (lbf/in-width) 1" x 6" specimens; Cond. 2h @ -0.4±3.6°F; Test @ -0.4±3.6°F; Rate = 0.08in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	94	100	110	113	91	102	10	≥ 70	
	CMD	78	70	72	73	86	76	6	≥ 70	
Elongation, (%) 1" x 6" specimens; Cond. 2h @ -0.4±3.6°F; Test @ -0.4±3.6°F; Rate = 0.08in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	35	35	43	43	27	36	7	≥ 20	
	CMD	35	32	44	33	45	38	6	≥ 20	
Peak Load, (lbf/in-width) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	94	90	101	92	86	93	6	≥ 50	
	CMD	72	70	65	68	63	68	4	≥ 50	
Elongation, (%) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	55	56	62	52	53	56	4	≥ 35	
	CMD	63	62	51	55	46	55	7	≥ 35	
<i>Continued on next page</i>										

CURA-004-02-08

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Property	Test Method	Results							Requirement
		1	2	3	4	5	Avg.	St. Dev.	Type I, Grade G
Ultimate Elongation, (%) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.	
	MD	58	61	81	58	55	63	11	≥ 38
	CMD	66	66	54	59	49	59	8	≥ 38
Low Temperature Flexibility, [Pass/Fail] 1" x 6" specimens; Cond. 2h @ 0°F; Test weathering side away from mandrel; Test 180±5° over 1" ø in 2±1s @ 0°F; Visual Inspection in "flexed" position	ASTM D 5147	1	2	3	4	5			Pass = "none of the specimens show cracking"
	MD	Pass	Pass	Pass	Pass	Pass			Pass @ 0°F
	CMD	Pass	Pass	Pass	Pass	Pass			Pass @ 0°F

Notes: 1) N/A indicates Not Applicable; NT indicates Not Tested; As Agreed: as agreed by buyer and seller

CURA-004-02-08

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Statement of Compliance:

The products tested have demonstrated compliance with the physical property requirements of ASTM D 6164-05^{e1} and ASTM D 6164/D 6164M-11: *Standard Specification for Styrene Butadiene Styrene (SBS) Modified Bituminous Sheet Material Using Polyester Reinforcements*, Type I and Florida Building Code Test Protocols for High-Velocity Hurricane Zones, Test Application Standard (TAS) No. 110-2000 *Testing Requirements for Physical Properties of Roof Membranes, Insulation, Coatings, and Other Roofing Components*. The laboratory test results presented in this report are representative of the material supplied.

Signed: _____
Zachary R. Priest, P.E.
Florida Registered Professional Engineer
PE No.: 74021

Date: 04/27/2018



Report Issue History:

Issue #	Date	Pages	Revision Description (if applicable)
Original	04/27/2018	9	N/A

END OF REPORT

CURA-004-02-08

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.



CONSTRUCTION MATERIALS

TECHNOLOGIES

LABORATORY TEST REPORT

Report for: Curacreto, SA de CV
Av. 1 de Mayo #8A
Mexico City, Mexico 11870

Attention: Jorge A. Robles Ramos

Product Name:	Technoply SBS SP 400 Aluminum Flake	Manufacturer:	Curacreto, SA de CV
Date Received:	Jan. 3, 2018	Sampling:	Curacreto, SA de CV, Mexico City, Mexico
PRI-CMT Project No.:	CURA-006-02-01	Test Dates:	Jan. 3, 2017 – Apr. 25, 2018

Purpose: Evaluate the named products for compliance with **ASTM D 6164: Standard Specification for Styrene Butadiene Styrene (SBS) Modified Bituminous Sheet Material Using Polyester Reinforcements** and **ASTM D 5147 Section 13: Accelerated Weathering** as required by the **Florida Building Code Test Protocols for High-Velocity Hurricane Zones, Test Application Standard (TAS) No. 110-2000 Testing Requirements for Physical Properties of Roof Membranes, Insulation, Coatings, and Other Roofing Components.**

Test Methods: Testing was completed in compliance with ASTM D 6164-05^{e1} and ASTM D 6164/D 6164M-11: *Standard Specification for Styrene Butadiene Styrene (SBS) Modified Bituminous Sheet Material Using Polyester Reinforcements.* Test methods assigned or referenced include ASTM D 146: *Standard test Methods for Sampling and testing Bitumen-Saturated Felts and Woven Fabrics for Roofing and Waterproofing;* ASTM D 1204: *Standard Test Method for Linear Dimensional Changes of Nonrigid Thermoplastic Sheeting or Film at Elevated Temperature;* ASTM D 4073: *Standard Test Method for Tensile-Tear Strength of Bituminous Roofing Membranes;* ASTM D 4977: *Standard Test Method for Granule Adhesion to Mineral Surfaced Roofing by Abrasion;* ASTM D 5147: *Standard Test Methods for Sampling and Testing Modified Bituminous Sheet Materials;* ASTM D 5636: *Standard Test Method for Low Temperature Unrolling of Felt or Sheet Roofing and Waterproofing Materials;* and ASTM D 5869: *Standard Practice for Dark Oven Heat Exposure of Roofing and Waterproofing Materials.*

Sampling: Product samples were provided by Curacreto, SA de CV from Mexico City, Mexico.

CURA-006-02-01

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Results:

Property	Test Method	Results							Requirement	
									Type I, Grade G	
Physical Properties – Before Heat Conditioning										
Peak Load, (lbf/in-width) 1" x 6" specimens; Cond. 2h @ -0.4±3.6°F; Test @ -0.4±3.6°F; Rate = 0.08in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	111	120	109	114	110	113	4	≥ 70	
	CMD	79	83	86	94	98	88	8	≥ 70	
Elongation, (%) 1" x 6" specimens; Cond. 2h @ -0.4±3.6°F; Test @ -0.4±3.6°F; Rate = 0.08in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	44	41	38	40	37	40	3	≥ 20	
	CMD	24	34	43	44	55	40	12	≥ 20	
Peak Load, (lbf/in-width) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	70	81	77	91	78	80	8	≥ 50	
	CMD	54	61	54	63	66	60	5	≥ 50	
Elongation, (%) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	48	68	63	70	59	62	9	≥ 35	
	CMD	48	60	49	70	76	61	13	≥ 35	
<i>Continued on next page</i>										

CURA-006-02-01

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Property	Test Method	Results							Requirement	
		1	2	3	4	5	Avg.	St. Dev.	Type I, Grade G	
Ultimate Elongation, (%) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	152	378	181	107	441	252	148	≥ 38	
	CMD	182	132	152	155	172	159	20	≥ 38	
Tear Strength, (lbf) 3" x 8" specimens with assigned notch; Cond. 4h @ 73.4±3.6°F & 50±5%RH; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	106	101	104	93	103	101	5	≥ 55	
	CMD	126	135	128	127	130	129	4	≥ 55	
Low Temperature Flexibility, (Pass/Fail) 1" x 6" specimens; Cond. 2h @ 0°F; Test weathering side away from mandrel; Test 180±5° over 1" ø in 2±1s @ 0°F; Visual Inspection in "flexed" position	ASTM D 5147	1	2	3	4	5			Pass = "none of the specimens show cracking"	
	MD	Pass	Pass	Pass	Pass	Pass			Pass @ 0°F	
	CMD	Pass	Pass	Pass	Pass	Pass			Pass @ 0°F	
Dimensional Stability, (%) 10" x 10" specimens; Cond. 40h @ 73.4±3.6°F & 50±5%RH; Test 24h±15min @ 176±3.6°F	ASTM D 1204/ ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	0.0	0.0	0.0	0.0	0.1	0.0	0.0	≤ 1	
	CMD	0.0	0.0	0.1	0.1	0.1	0.1	0.0	≤ 1	
<i>Continued on next page</i>										

CURA-006-02-01

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Property	Test Method	Results							Requirement	
		1	2	3	4	5			Type I, Grade G	
Compound Stability, [Pass/Fail] 2.0±0.05" x 3.0±0.05" specimens; Cond. 4h @ 73.4±3.6°F & 50±5%RH; Test 2h,15min±5min @ 215±5°F	ASTM D 5147	1	2	3	4	5				Pass = no failures showing signs of flowing, dripping, or drop formation
	MD	Pass	Pass	Pass	Pass	Pass				Pass
	CMD	Pass	Pass	Pass	Pass	Pass				Pass
Granule Embedment (g) Grade G products only; 2" x 9" specimens; Cond. 30min @ 73.4±3.6°F; Test 50 complete cycles	ASTM D 4977/ ASTM D 5147	1	2	AVG.						
		0.4	0.4	0.4						≤ 2
Physical Properties – After Heat Conditioning										
Heat Conditioning Exposure: 90±0.25d @ 158±5°F	ASTM D 5869/ ASTM D 5147									
Peak Load, (lbf/in-width) 1" x 6" specimens; Cond. 2h @ -0.4±3.6°F; Test @ -0.4±3.6°F; Rate = 0.08in/min ±3%	ASTM D 5147	1	2	3	4	5	AVG.	St. Dev.		
	MD	116	115	113	101	113	112	6		≥ 70
	CMD	79	74	76	74	78	76	3		≥ 70
Elongation, (%) 1" x 6" specimens; Cond. 2h @ -0.4±3.6°F; Test @ -0.4±3.6°F; Rate = 0.08in/min ±3%	ASTM D 5147	1	2	3	4	5	AVG.	St. Dev.		
	MD	35	34	36	24	35	33	5		≥ 20
	CMD	27	16	20	15	24	20	5		≥ 20
<i>Continued on next page</i>										

CURA-006-02-01

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Property	Test Method	Results							Requirement	
									Type I, Grade G	
Peak Load, (lbf/in-width) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	107	93	82	85	91	91	10	≥ 50	
	CMD	77	69	69	62	74	70	6	≥ 50	
Elongation, (%) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	54	44	44	44	49	47	5	≥ 35	
	CMD	44	53	51	40	52	48	6	≥ 35	
Ultimate Elongation, (%) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	56	52	48	46	51	51	4	≥ 38	
	CMD	48	57	54	43	55	51	6	≥ 38	
Low Temperature Flexibility, [Pass/Fail] 1" x 6" specimens; Cond. 2h @ 0°F; Test weathering side away from mandrel; Test 180±5° over 1" ø in 2±1s @ 0°F; Visual Inspection in "flexed" position	ASTM D 5147	1	2	3	4	5			Pass = "none of the specimens show cracking"	
	MD	Pass	Pass	Pass	Pass	Pass			Pass @ 0°F	
	CMD	Pass	Pass	Pass	Pass	Pass			Pass @ 0°F	
<i>Continued on next page</i>										

CURA-006-02-01

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Property	Test Method	Results					Requirement			
							Type I, Grade G			
Physical Properties – Other										
Unrolling, [Pass/Fail] 10±1/8" x 18±1/8" specimens; Cond. 24h @ 73.4±3.6°F & 50±5%RH; Test Cond. 2h @ Temp±1°F; Test unroll in 4-6s; Visual Inspection in "unrolled" position	ASTM D 5636/ ASTM D 5147	1	2	3	4					Pass = "finished product shall not crack nor be so sticky as to cause tearing or other material damage upon being unrolled at any temperature between 40 and 140°F"
	Temp=40°F	Pass	Pass	Pass	Pass					Pass
	Temp=140°F	Pass	Pass	Pass	Pass					Pass
Dimensions and Masses										
Thickness, (mils) 27-1/2" x manufacture width; 5 measurement points	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
		147	147	144	146	145	146	1	≥ 130	
Net Mass, (lb/100ft ²) 1 specimen; manufacture roll	ASTM D 228									
		82								≥ 75
Bottom Coating Thickness, (mils) Heat Welding Application Products; 6" x manufacture width; 5 measurement points	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
		49	46	47	46	49	47	2	≥ 40	
<i>Continued on next page</i>										

CURA-006-02-01

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Property	Test Method	Results							Requirement	
									Type I, Grade G	
Physical Properties – After Accelerated Weathering										
Xenon Arc Weathering Exposure: 83±0.35d @ Cycle A	ASTM D 4798/ ASTM D 5147									
Peak Load, (lbf/in-width) 1" x 6" specimens; Cond. 2h @ -0.4±3.6°F; Test @ -0.4±3.6°F; Rate = 0.08in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	104	113	118	105	112	111	6	≥ 70	
	CMD	93	88	87	63	69	80	13	≥ 70	
Elongation, (%) 1" x 6" specimens; Cond. 2h @ -0.4±3.6°F; Test @ -0.4±3.6°F; Rate = 0.08in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	37	30	33	19	38	31	8	≥ 20	
	CMD	39	32	35	13	21	27	14	≥ 20	
Peak Load, (lbf/in-width) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	90	112	88	88	81	92	12	≥ 50	
	CMD	66	71	76	78	66	72	5	≥ 50	
Elongation, (%) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.		
	MD	59	66	52	56	57	58	5	≥ 35	
	CMD	64	62	64	67	56	63	4	≥ 35	
<i>Continued on next page</i>										

CURA-006-02-01

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Property	Test Method	Results							Requirement
									Type I, Grade G
Ultimate Elongation, (%) 1" x 6" specimens; Cond. 2h @ 73.4±3.6°F; Test @ 73.4±3.6°F; Rate = 2.0in/min ±3%	ASTM D 5147	1	2	3	4	5	Avg.	St. Dev.	
	MD	96	74	84	114	100	94	15	≥ 38
	CMD	71	73	72	76	66	72	4	≥ 38
Low Temperature Flexibility, [Pass/Fail] 1" x 6" specimens; Cond. 2h @ 0°F; Test weathering side away from mandrel; Test 180±5° over 1" ø in 2±1s @ 0°F; Visual Inspection in "flexed" position	ASTM D 5147	1	2	3	4	5			Pass = "none of the specimens show cracking"
	MD	Pass	Pass	Pass	Pass	Pass			Pass @ 0°F
	CMD	Pass	Pass	Pass	Pass	Pass			Pass @ 0°F

Notes: 1) N/A indicates Not Applicable; NT indicates Not Tested; As Agreed: as agreed by buyer and seller

CURA-006-02-01

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Statement of Compliance:

The products tested have demonstrated compliance with the physical property requirements of ASTM D 6164-05^{e1} and ASTM D 6164/D 6164M-11: *Standard Specification for Styrene Butadiene Styrene (SBS) Modified Bituminous Sheet Material Using Polyester Reinforcements*, Type I and Florida Building Code Test Protocols for High-Velocity Hurricane Zones, Test Application Standard (TAS) No. 110-2000 *Testing Requirements for Physical Properties of Roof Membranes, Insulation, Coatings, and Other Roofing Components*. The laboratory test results presented in this report are representative of the material supplied.

Signed: _____
Date: _____



Zachary R. Priest, P.E.
Florida Registered Professional Engineer
PE No.: 74021

STATE OF FLORIDA
PROFESSIONAL ENGINEER

Report Issue History:

Issue #	Date	Pages	Revision Description (if applicable)
Original	04/27/2018	9	N/A

END OF REPORT

CURA-006-02-01

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.